

**L.B.WHITE****TORCHMAN™, BERTHA™, AND INDUSTRIAL TORCHES**

	<b>Torchman 200</b>	<b>Torchman 500</b>	<b>Torchman 500 Delux</b>	<b>Bertha 200</b>	<b>Bertha 500</b>	<b>Industrial 250</b>	<b>Industrial 400</b>	<b>Industrial 400-M</b>	<b>Industrial 365N</b>
<b>Btu/h Rating</b>	200,000	500,000	500,000	200,000	500,000	250,000	400,000	400,000	365,000
<b>Fuel Consumption (max.)</b>									
<b>Liquid Propane Gas (lbs./hr.)</b>	9.3	23.2	23.2	9.3	23.2	11.6	18.5	18.5	–
<b>Natural Gas (cu.ft./hr.)</b>	–	–	–	–	–	–	–	–	365.0
<b>Ignition Type</b>	Manual	Manual	Manual	Manual	Manual	Manual	Pilot	Manual	Pilot
<b>Inlet Gas Pressure</b>									
<b>Propane min./max. (PSIG)</b>	Tank	Tank	Tank	25.0	25.0	23.0	25.0	25.0	–
<b>Natural Gas min./max. (PSIG)</b>	–	–	–	–	–	–	–	–	7.0
<b>Head Type</b>	Steel	Steel	Steel	Cast Iron	Cast Iron	Cast Iron 90° Head	Cast Iron	Cast Iron	Cast Iron
<b>Control Valve</b>	S	S	S	S	S	S	S	S	S
<b>Excess Flow Valve</b>	S	S	S	S	S	S	S	S	-
<b>Regulator</b>									
<b>Preset</b>	–	–	–	O*	O*	S	S	S	S
<b>POL</b>	S	S	S	S***	S***	S	S	S	-
<b>Gas Hose (10ft.- other lengths available)</b>	S	S	S	S	S	S	S	S	O
<b>Thermocouple</b>	–	–	–	–	–	S	S	S	S
<b>Support Handle</b>	–	–	S	–	–	–	–	–	–
<b>Assembled Length (in.)</b>	36.0	36.0	41.0	20.0	22.0	17.5	22.0	22.0	26.0
<b>Net Weight (lbs.)</b>	5.0	5.5	6.0	5.5	7.0	7.5	10.5	10.5	10.5
<b>Shipping Weight (lbs.)</b>									
<b>Bulk Packed**</b>	5.0	5.5	6.0	5.5	7.0	–	–	–	–
<b>Individually Packed</b>	–	–	–	–	–	9.5	10.5	10.5	12.5
<b>Skin Packed**</b>	5.5	6.0	–	6.0	7.5	–	–	–	–

\* Recommended option

\*\*Bulk Packed sold in packages of 8 torches; Skin Packed sold in packages of 4 torches.

\*\*\* Included standard with optional regulator assembly

S = Standard O = Optional



Quality heaters you can count on.

Your L.B. White Dealer:

W6636 L.B. White Rd., Onalaska, WI 54650  
 (800) 345-7200  
 (608) 783-5691  
 (608) 783-6115, fax  
 www.lbwhite.com

© 2010 L.B. White Co.  
 All rights reserved.  
 All specifications are subject  
 to change without notice.

F5129.0710